

Product Overview

NSPAS1 is a calibrated absolute pressure sensor series product launched by NOVOSENSE for vacuum boost, motorcycle MAP and Auto TMAP market. This series uses an automotive-grade ASIC to calibrate and compensate the MEMS sensor element, the pressure signal from 10kPa to 400kPa can be converted into an analog output signal (0~5V) with a customizable output range. While ensuring the reliability of the product, the two chips are integrated and packaged, reduces the package size greatly. This series provides outstanding performance in terms of initial accuracy and suits applications with harsh automotive temperature and stress conditions needing small drift over lifetime. Reliability test according to AEC-Q100 standard.

Key Features

- High precision pressure sensing
Better than $\pm 1\%$ F.S. (0°C to 85°C)
Better than $\pm 1.5\%$ F.S. (-40°C to 125°C)
- Large temperature range (-40°C to 125°C)
- Over-voltage and Reverse voltage protection
between -24V to 28V
- Directly supplied by high voltage up to 18V (absolute analog output)
- Better than 0.8ms response time
- Ratiometric/Absolute analog output
- Clamping
- AEC-Q100 qualified

Applications


- Motorcycle TMAP applications
- Temperature manifold pressure sensor (TMAP¹)
- ECU barometric absolute pressure (ECU-BAP)
- Canister desorption pressure detection
- Battery pressure sensor
- Seat airbag pressure detection
- Industrial control

1. Not suitable for **harsh media applications** like fresh air mixed with high concentrations of corrosive gases such as engine exhaust gas or halogens.

Device Information

Part Number	Package	Body Size
NSPAS1	7373SOP8	7.30mm × 7.30mm

Outline



INDEX

1. PIN CONFIGURATION AND FUNCTIONS	3
2. ABSOLUTE MAXIMUM RATINGS	4
3. RECOMMENDED OPERATING CONDITIONS.....	4
4. SPECIFICATIONS.....	5
4.1. ELECTRICAL CHARACTERISTIC.....	5
5. FUNCTION DESCRIPTION	6
5.1. OVERVIEW.....	6
5.2. TRANSFER FUNCTION	6
5.3. ACCURACY	7
5.4. ALARM	9
6. TYPICAL APPLICATION.....	9
6.1. APPLICATION CIRCUIT	9
6.2. RECOMMENDED FOOTPRINT	10
6.3. SOLDERING PARAMETERS.....	10
7. PACKAGE INFORMATION.....	11
8. ORDER INFORMATION	12
9. IDENTIFICATION CODE	13
10. PACKING INFORMATION	13
11. REVISION.....	14

1. Pin Configuration and Functions




Fig 1.1 Pin Definition (Top view)

Table 1.1 Pin Description

Pin No.	Pin Name	Description
1	GND	Ground
2	GND	Ground
3	VOUT	Analog output
4	NC	No connect
5	OWI	One wire interface (leave floating)
6	VDDHV	Power supply with OVP/RVP
7	NC	No connect
8	NC	No connect

2. Absolute Maximum Ratings

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Supply voltage	VDDHV	-24		28	V	70°C, 1 hour
		-30		36	V	70°C, 1 minute
Analog pin voltage	VOUT	-0.3		5.3	V	25°C, VDDHV>5V
Analog output current limit				25	mA	
Proof pressure	P _{proof}	600			kPa	
Burst pressure	P _{burst}	800			kPa	
ESD susceptibility	HBM	±2			kV	
	CDM	±750			V	Corner pins
		±500			V	All other pins
Storage temperature	T _{tsg}	-40		125	°C	

3. Recommended Operating Conditions

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Supply voltage	VDDHV	4.5	5	5.5	V	
Operating pressure	P _{amb}	10		400	kPa	
Operating temperature	T _{opr}	-40		125	°C	

4. Specifications

4.1. Electrical Characteristic

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Output voltage range	V _{OUT}	0.05		4.95	V	
Accuracy pressure ¹	ACC _P	-1%		1%	%F.S.	@0°C ~85°C
		-1.5%		1.5%	%F.S.	@-40°C ~125°C
Power on reset	VDDHV _{POR}		2.5		V	
Operating current ²	I _{avdd}	2.6	3.1	3.6	mA	@25°C
Output RMS noise	V _{rms}		0.5		mV	
Output load resistance	R _{load}	1			kOhm	
Output load capacitance	C _{load}			150	nF	
Output short current limit	I _{short_lmt}	10		25	mA	Output short to VDDHV or GND
Clamp high level	V _{clamph}	50%		100%	%VDDHV	
Clamp low level	V _{clAMPL}	0%		50%	%VDDHV	
Clamp level error	ΔV _{clamp}		±40		mV	@VDDHV=5V
Power up time ²	T _{UP}	8	10	12	ms	@25°C
Response time	T _{RESP}			0.8	ms	
EEPROM data retention	T _{live}	10			years	@150°C

1. Pressure accuracy is qualified with part number NSPAS1N115RR01. For pressure accuracy of different part number, please refer to complete part number list at chapter 8.
2. These characteristics are tested at room temperature.

5. Function Description

5.1. Overview

NSPAS1 uses a MEMS piezoresistive absolute pressure sensor element as a pressure sensitive component that provide an original signal output that is proportional to ambient pressure. The built-in conditioning IC drives the sensitive component and amplifies, temperature compensates, and linearizes the original signal to output a voltage signal that is linear with the applied pressure.




Fig 5.1 Product Function Block Diagram

5.2. Transfer Function

NSPAS1 series device is fully calibrated on delivery. The sensor has a linear transfer function between the applied pressure and the output signal:

$$\text{Ratiometric: } VOUT = (A \times P + B) \times VDDHV$$

$$\text{Absolute: } VOUT = (A \times P + B) \times 5$$

Note: 1) P is the pressure value, absolute pressure, range: 10kPa~400kPa; the transfer function is only established in the pressure range.

2) VDDHV must in the operating voltage range;

Table 5.1 NSPAS1N115RR01 Transfer Function Coefficient

Product Type	Pressure Range		Output Range		Comments	
	P_L	P_H	O_L	O_H	A	B
NSPAS1N115RR01	10kPa	115kPa	0.4V	4.65V	0.008095	-0.00095




Fig 5.2 NSPAS1N115RR01 Transfer Function

5.3. Accuracy

Factors affecting the accuracy of NSPAS1 series products include power supply voltage (ratiometric error), pressure, temperature and aging effects. Standard output refers to the theoretical voltage output calculated by the transfer function of the pressure in the range. The error equals the deviation between the measured output voltage value and the specified output voltage value. The accuracy in the following analysis is in a typical application circuit.

5.3.1 Ratiometric Error

Ideally the sensor is ratiometric - the output (VOUT) scales by the same ratio that VDDHV increases or decreases. The ratiometric error is defined as the difference between the ratio that VDDHV changed and the ratio that VOUT changed, expressed as a percentage. The calculation formula is as follows:

$$E_{RAT}(\%) = ((VOUT(@VDDHV) - VOUT(@5V)) \times VDDHV/5V) / 5V \times 100\%$$

The output voltage VOUT is ratiometric to VDDHV. VDDHV must be in the operating range.

Table 5.2 Ratiometric Output Error

Supply Voltage (V)	Max. Ratiometric Error $E_{RAT}(\%)$ @ $VDDHV_{TYP}$
$VDDHV_{MIN}$	$\pm 0.5\%$
$VDDHV_{TYP}$	0
$VDDHV_{MAX}$	$\pm 0.5\%$




Fig 5.3 Ratiometric Error

5.3.2 Overall Accuracy

The accuracy error includes errors introduced by all influencing factors within the operating range of pressure and temperature, including:

Pressure: Output deviation from target transfer function over the specified pressure range

Temperature: Output deviation over the temperature range

Aging: Parameter drift over life time

Ps: Ratiometric signal error is not included in the overall accuracy. For error measurements, the supply voltage must have the nominal value ($VDDHV = 5V$).

Table 5.3 Accuracy

Temperature (°C)	Error (%F.S.)
-40	1.50
0	1.00
85	1.00
125	1.50




Fig 5.4 Accuracy for Pressure Acquisition

5.4. Alarm

NSPAS1 series have output alarm functions; when MEMS differential signal short to VDDHV/GND, the Vout will be pulled up to high voltage (4.9V@VDDHV=5V). The alarm function is OFF on default in order to optimize the response speed.

6. Typical Application

6.1. Application Circuit




Fig 6.1 Application Circuit

Note :

- 1) For applications with higher ESD requirements, can add TVS between VOUT and GND and between VDDHV and GND.
- 2) Please contact NOVOSENSE for detailed peripheral recommended circuit.

6.2. Recommended Footprint




Fig 6.2 Footprint mm

6.3. Soldering Parameters

Table 6.1 Soldering Parameters

Reflow Condition		Lead-free Assembly
Pre Heat	Temperature Min (Ts(min))	150°C
	Temperature Max (Ts(max))	200°C
	Time (min to max) (ts)	60 – 180 secs
Average ramp up rate (Liquidus Temp (T _L) to peak		3°C/second max
T _s (max)to T _L - Ramp-up Rate		3°C/second max
Reflow	Temperature (T _L) (Liquidus)	217°C
	Time (min to max) (t _L)	60 – 150 seconds
Peak Temperature (T _P)		260°C
Time within 5°C of actual peak Temperature (tp)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T _P)		8 minutes Max.
Do not exceed		260°C




Fig 6.3 Soldering Profile

7. Package Information




Fig 7.1 Package Outline mm

8. Order Information

Product Type	Output Type	Pressure Range		Output Range		Clamp Level		Gain and Offset		Supply Voltage	Accuracy	
		P _L	P _H	O _L	O _H	V _{CL}	V _{CH}	A	B		0~85 °C	-40~125 °C
NSPAS1N115RR01	Ratiometric	10.00kPa	115.00kPa	0.400V	4.650V	6%	94%	0.008095	-0.000952	5.0V	±1.0%	±1.5%
NSPAS1N115RR02	Ratiometric	15.00kPa	115.00kPa	0.200V	4.700V	4%	94%	0.009000	-0.095000	5.0V	±1.0%	±1.5%
NSPAS1N300RR10	Ratiometric	50.00kPa	300.00kPa	0.400V	4.650V	0%	100%	0.003400	-0.090000	5.0V	±1.0%	±1.5%
NSPAS1N120RRA1	Ratiometric	13.33kPa	119.99kPa	1.000V	4.200V	0%	100%	0.006000	0.120002	5.0V	±1.0%	±1.5%
NSPAS1N200RR25	Ratiometric	80.00kPa	200.00kPa	0.250V	4.750V	5%	95%	0.007500	-0.550000	5.0V	±1.0%	±1.5%
NSPAS1N115RR27	Ratiometric	20.00kPa	115.00kPa	0.400V	4.650V	2%	97%	0.008947	-0.098947	5.0V	±1.0%	±1.5%
NSPAS1N165RRS1	Ratiometric	50.00kPa	165.00kPa	0.500V	4.500V	7%	94%	0.006957	-0.247826	5.0V	±1.0%	±1.5%
NSPAS1N400RR33	Ratiometric	50.00kPa	400.00kPa	0.500V	4.500V	6%	94%	0.002286	-0.014286	5.0V	±1.0%	±1.5%
NSPAS1N105RR35	Ratiometric	20.00kPa	105.00kPa	0.400V	4.650V	0%	100%	0.010000	-0.120000	5.0V	±1.0%	±1.5%
NSPAS1N350RR46	Ratiometric	44.80kPa	350.00kPa	0.500V	4.500V	5%	95%	0.002621	-0.017431	5.0V	±1.0%	±1.5%


Please scan the following QR code or visit the download link for complete part number list.

<https://www.novosns.com//Public/Uploads/uploadfile4/nspas1-series.pdf>




NSPAS1 Series

Naming Convention:




9. Identification Code



NSPAS1NAAAAAAA: Product Type No.


BBBBBBBBBBB: Date Code

10. Packing Information




Part NO.	Package type	W (mm)	P0 (mm)	A0 (mm)	P (mm)	E (mm)	B0 (mm)	F (mm)	P2 (mm)	K0 (mm)	D0 (mm)	T (mm)
NSPAS1N165RRS1	SOP8	24±0.30	4±0.10	7.65±0.1	12±0.03	1.75±0.1	11±0.10	11.5±0.10	2±0.03	3.7±0.1	1.5+0.1	0.35±0.05

There is no component at the head and the tail of each tape/reel, where the space is 50cm, as shown in the following figure.



Pin1 is located at the second quadrant, as shown in the following figure.



Minimum ordering quantity(MOQ):1000EA.

Standard pack quantity(SPQ): 1000EA

11. Revision

Revision	Description	Date
0.1	Initial Version.	2018/6/18
1.0	Formal release.	2018/12/8
2.0	Update the pin definition, block diagram, application circuit, outline drawing, package drawing packaging information.	2019/8/29
2.1	Part number update.	2020/3/6
2.2	Add clamping, diagnostic alarm function; ESD; Add power up time description.	2020/4/28
3.0	Change series naming rules.	2020/5/17
3.1	Add NSPAS1N135RT09、NSPAS1N300RT10 Part No.	2020/6/15
3.2	Add NSPAS1N120RTA1 Part No.	2020/7/8
3.3	Add NSPAS1N360RT11~NSPAS1N400RT21 Part No.	2020/12/28
3.4	Update format, font typical and application.	2021/2/7
3.5	Update format, LOGO.	2021/06/15
3.6	Update clamp voltage format; Update application circuit; Add soldering parameter; Add tape/reel package information	2022/05/11
3.7	Update pin description with OWI interface; Update order information; Remove tube packaging information	2023/01/31
3.8	Update order information and add barcode.	2023/04/21
3.9	Update pin description.	2023/08/16
4.0	Add comments for TMAP application; Remove VBS application; Update typical application circuit; Update naming convention description.	2024/4/29

IMPORTANT NOTICE

The information given in this document (the “Document”) shall in no event be regarded as any warranty or authorization of, express or implied, including but not limited to accuracy, completeness, merchantability, fitness for a particular purpose or infringement of any third party’s intellectual property rights.

Users of this Document shall be solely responsible for the use of NOVOSENSE’s products and applications, and for the safety thereof. Users shall comply with all laws, regulations and requirements related to NOVOSENSE’s products and applications, although information or support related to any application may still be provided by NOVOSENSE.

This Document is provided on an “AS IS” basis, and is intended only for skilled developers designing with NOVOSENSE’s products. NOVOSENSE reserves the rights to make corrections, modifications, enhancements, improvements or other changes to the products and services provided without notice. NOVOSENSE authorizes users to use this Document exclusively for the development of relevant applications or systems designed to integrate NOVOSENSE’s products. No license to any intellectual property rights of NOVOSENSE is granted by implication or otherwise. Using this Document for any other purpose, or any unauthorized reproduction or display of this Document is strictly prohibited. In no event shall NOVOSENSE be liable for any claims, damages, costs, losses or liabilities arising out of or in connection with this Document or the use of this Document.

For further information on applications, products and technologies, please contact NOVOSENSE (www.novosns.com).

Suzhou NOVOSENSE Microelectronics Co., Ltd